



NOTE:
 1.* Important Dimension.
 (* 為重點檢尺寸)
 2.適用板厚 2.5mm 以下

8	Brown	棕	8	Twist 對線
7	White/Brown	白/棕	7	Twist 對線
6	Green	綠	6	Twist 對線
5	White/Blue	白/藍	5	Twist 對線
4	Blue	藍	4	Twist 對線
3	White/Green	白/綠	3	Twist 對線
2	Orange	桔	2	Twist 對線
1	White/Orange	白/桔	1	Twist 對線
Conn1	Wire Color		Conn2	

7	Shrink Tube	Black	1	TUB060001XX
6	Cable	Grey	1	WCA0159XX02
5	Plug		1	CPLRJ10G001
4	PCB		1	ZPB0026XXXX
3	Gasket	Black	1	DGA0014EP70
2	Nut	Black	1	ANB138XXX01
1	Clip Socket	Black	1	AAA216XXXX01

NO	NAME	COLOR	SPECIFICATION	QTY	NOTE
7	Shrink Tube	Black	ø6.0*10mm	1	TUB060001XX
6	Cable	Grey	CAT 5 UTP 24AWG*4P OD=5.3±0.20mm,L=225±5mm	1	WCA0159XX02
5	Plug		8P8C Unshielded Plug Gold Flash (Short Type)	1	CPLRJ10G001
4	PCB		Cat 5e PCB	1	ZPB0026XXXX
3	Gasket	Black	EPDM	1	DGA0014EP70
2	Nut	Black	Nylon+GF	1	ANB138XXX01
1	Clip Socket	Black	PC+ABS,UL 94HB,UV	1	AAA216XXXX01

UNIT : mm		TITLE	LWRJ45-IU21RX To 8P8C RJ45 Unshield	
TOLERANCE	±0.5mm	SCALE	Free	SHEET 1 OF 1
REV.	A	DATE		SIZE A4
tuner Networks(USA)				
ITEM NO	RJ45-002M-IN	DRAWN BY	Yi Chuan Lee	
DWG NO	RJ45-002M-IN	CHECKED BY		
CUSTOMER	LS	APPROVED BY		
DATE		DATE	2004/04/20	