

EZ1, EZ2, EZ3 Product Comparison

| | EZ1 | EZ2 | EZ3 |
|--|---------|---------|---------|
| Physical | | | |
| 2.4GHz – 802.11 b/g | ✔ | ✔ | ✔ |
| Output Power | 100mW | 250mW | 250mW |
| Power Over Ethernet Passive | 12-18V | 12-18V | 12-48V |
| Power Over Ethernet 802.3af | ✘ | ✘ | ✔ |
| FLASH | 2MB | 2MB | 4MB |
| RAM | 8MB | 16MB | 32MB |
| Chipset | RTL8186 | RTL8186 | RTL8186 |
| Operational Modes | | | |
| Bridge Mode – BR+ (AP, AP Client, WDS, WDS+AP, Universal Repeater) | ✔ | ✔ | ✔ |
| Access Point Router Mode – AR+ (AP, Universal Repeater) | ✘ | ✔ | ✔ |
| Client Router Mode – CR+ (AP Client, Universal Repeater) | ✘ | ✔ | ✔ |
| Wireless | | | |
| Basic Settings | ✔ | ✔ | ✔ |
| Advanced Settings | ✔ | ✔ | ✔ |
| Security Settings | ✔ | ✔ | ✔ |
| Site Survey | ✔ | ✔ | ✔ |
| Access Control | ✔ | ✔ | ✔ |
| Antenna Alignment | ✔ | ✔ | ✔ |
| Administration / Management | | | |
| Web interface | ✔ | ✔ | ✔ |
| Telnet | ✔ | ✔ | ✔ |
| SSH | ✘ | ✔ | ✔ |
| SNMP | ✘ | ✔ | ✔ |
| Networking | | | |
| Bridging | ✔ | ✔ | ✔ |
| Routing / NAT | ✘ | ✔ | ✔ |
| HotSpot | ✘ | ✘ | ✔ |
| Firewall (in AR+ or CR+ modes) | | | |
| Port Filtering | ✘ | ✔ | ✔ |
| IP Filtering | ✘ | ✔ | ✔ |
| MAC Filtering | ✘ | ✔ | ✔ |
| Port Forwarding | ✘ | ✔ | ✔ |
| DMZ | ✘ | ✔ | ✔ |
| Bandwidth Control | ✘ | ✔ | ✔ |
| QoS | ✘ | ✔ | ✔ |
| VPN | ✘ | ✘ | ✔ |