Datasheet

UACC-PoE+-2.5G

2.5G PoE+ Adapter (30W)

Specifications:	
Dimensions	93 x 62 x 35 mm
Weight	156 g
Output Voltage	48V DC @ 0.65A
LAN Activity Indicator	No
Gigabit LAN Port	Yes, up to 2.5 GbE
Remote Reset Capability	No
Reset Button	No
Rated Voltage	100—240V AC @ 50/60Hz
Input Current	0.75A max.
Inrush Current	<150A peak @ 230V AC
Efficiency	>87%
Output Ripple	1% max.
Switching Frequency	65 kHz max.
Line Regulation	≤ 1%
Load Regulation	≤ 3%
2-Pair Powering	Pins 4, 5 (+) and 7, 8 (-)
4-Pair Powering	No
Data In / PoE	RJ45 shielded socket
Surge Protection	Difference and common mode
Clamping Protection	11V data, 60V power
Max. Surge Discharge	1500A (8/20 µs) power
Peak Pulse Current	36A (10/1000 µs) data
Shunt Capacitance	<5 pF data
Response Time	<1 ns
Ambient Operating Temperature	0°C to 40°C
Storage Temperature	-30°C to 70°C
Ambient Operating Humidity	10 to 95% non condensing
Certifications	CE, FCC, IC, UL, UKCA, KC, CCC, RoHS

Datasheet

