

Features

Over-Voltage Protection
Over-Current Protection

Short-circuit Protection
100%Hi-pot & ATE(Chroma)Tested

100%Burn-in under High
Ambient Temperature(45°C)

Low Ripple/Noise
MTBF Above 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

CEC IV and V Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PA1015 Series

Direct Plug-In Type
for Europe



Specification

Model No Part No Item	PA1015-1DE		PA1015-2DE		PA1015-3DE	
	PA1015-030DEB~ PA1015-069DEB		PA1015-070DEB~ PA1015-149DEB		PA1015-150DEB~ PA1015-300DEB	
	Output Voltage	3.0~4.5V	4.6~6.9V	7.0~10.0V	10.1~14.9V	15.0~21.0V
Output Current(Max.)	2.6A	2.6A	2.15A	1.48A	1.0A	0.72A
Output Power(Max.)	15W		18W		18W	
Input Voltage	AC90~264V					
Input Frequency	47~63Hz					
Input Current	0.4A Maximum					
Inrush Current	40A Maximum					
Line Regulation	1% Maximum					
Ripple&Noise	1% Maximum					
Load Regulation	5% Maximum					
Efficiency	70~82%					
Operating Temperature	0~40℃					
Storage Temperature	-20~85℃					
Over-Voltage Protection	Auto Recovery					
Short-circuit Protection	Auto Recovery					
Safety Standard	CB,PSE					
EMC(EMI/EMS)	FCC,CE,C-Tick,VCCI					

機種編碼 Products code:

